

ORION™ SERIES

**HR & HR-i Series · (External Calibration)
(NTEP CofC# 97-084)**



- Percentage and Counting Modes
- Digital Preset Tare
- One Touch Printing
- Last Digit Suppression
- Standard Underhook
- Optional Rechargeable Battery Pack
- GLP/LIMS/ISO Compliant
- RS-232C Option or Standard
- 5 Year Warranty

Model	Description	Pan Size	Price	Discount
HR-60	60g x 0.1mg (NTEP CofC # 97-084) e = .001g	Ø 3.3"	\$1,825	A
HR-60-C	60g x 0.1mg with RS-232C	Ø 3.3"	\$1,925	A
HR-120	120g x 0.1mg	Ø 3.3"	\$2,225	A
HR-120-C	120g x 0.1mg with RS-232C	Ø 3.3"	\$2,325	A
HR-200	210g x 0.1mg	Ø 3.3"	\$2,395	A
HR-200-C	210g x 0.1mg with RS-232C	Ø 3.3"	\$2,495	A
HR-202i	220g/51g x 0.1mg/0.01mg Semi-micro with R-232C	Ø 3.6"	\$4,345	A
HR-300i	320g x 0.1mg with RS-232C	Ø 3.6"	\$3,895	A
HR-03	Serial Interface (RS-232C) for HR-60/120/200		\$155	C
HR-05	20mA Current Loop Interface for HR-60/120/200		\$119	C
HR-09	Internal NiCd Battery for HR-60, HR-60-C, HR-120, HR-120-C, HR-200, HR-200-C only		\$455	C
AD-100-2	Anti-Theft Device		\$65	G
AD-1653	Density Determination Kit		\$525	C
AD-1682	External Rechargeable Battery Pack		\$645	C
AD-8920A	Universal Remote Display		\$250	C
AD-1683	Static Eliminator		\$1,195	C
AD-8922A	Remote Controller		\$600	C
CC:103E	Storage/Carrying Case for HR-60, HR-120, HR-200 and -C versions only (While Supplies Last)		\$339	G
TB:248	HR AC Adapter (120V / 220V) - Standard with unit		\$39	G
TB:136C	HR-i AC Adapter (120V) - Standard with unit		\$39	G
TB:137	HR-i AC Adapter (220V)		\$49	G
AX-USB-2920-25P	USB to 25 pin RS-232 Converter		\$69	G

Note: NTEP Approved units in red.